

Microbox



- Fanless
- Support VESA mounting hole
- Compact Flash Slot
- 2 x RS-232 (Optional)
- On-board 10/100Mbps LAN
- PXE diskless boot
- Wireless LAN (optional)
- 2.5" Hard Disk
- Ultra Low Power (15 Watts)

The Microbox is a revolutionary device, that is especially designed for use where space and temperature are concerns. No matter if you are integrating an office, a public place, or public transportation, it can be easily fitted with a VESA LCD to bring you computer access at any time, any place.



System	
CPU	VIA Eden ULV 500MHz
BIOS	AMI BIOS
System Chipset	VIA CX700M
I/O Chip	Winbond W83697
System Memory	Onboard 512MB or 1GB DDR2

Audio	
AC97 2.2 (Codec)	VIA Vinyl VT1708
Audio Interface	Line out, Mic in

Mechanical & Environment	
Power Requirement	+5V @ 3.0A
Operating Temperature	0 ~ 60 °C
Operating Humidity	0% - 90% relative humidity, non-condensing
Size (W x H x D)	115x 115 x 35mm
Weight	505g
Certification	CE, FCC

I/O	
MIO	1 x EIDE, 1 x PS/2 K/B / Mouse 1 x Type I/II CF slot 2 x RS-232 Port (Opt. for eBox-4300JSK)
USB	3 x USB 2.0 Ports (two on front)

Ethernet	
Chipset	Realtek 8100B 10/100 Base-T
Remote Boot ROM	built-in boot ROM function, support PXE boot and Wake-up on LAN

